

Ultra Narrow Angle LED Floodlight / Gold

Stanley developed an LED for this ultra narrow-angle floodlight emitting a unique gold light.



■ Features

- Special golden color
- Floodlight with ultra narrow angle light distribution (Oval light distribution with 1/2 luminous intensity angle 4° *3°)
- Power saving, space saving, and light weight
- It can be installed everywhere; it can irradiate the aimed spot with reduced electricity

Developed with:
Motoko Ishii Lighting Design Inc.
Planned and Produced by:
Motoko Ishii & Akari Lisa Ishii

■ Applications

- Illumination (upper light, wallwasher, etc.)
- Stage light (stages, concerts, events, etc.)

■ Specifications [Gold + Color Variation]

- Space saving (downsized and thinner) 240*240*47mm
- Light weight 2.4kg (Included Bracket 3.7kg)

	GOLD	WHITE	RED	GREEN	BLUE
Beam angle	4° × 3° Oval	2.3°	2.5°	2.3°	2.3°
Luminous Intensity	667,000cd	918,000cd	180,000cd	518,000cd	235,000cd
Flux	3,300lm	1,720lm	680lm	950lm	410lm
Color temperature	—	6500K	—	—	—
Dominant wavelength	—	—	629nm	530nm	472nm
Power consumption	39.4W	17.9W	14.8W	18.7W	19.3W

This document is submitted in Oct .2018

STANLEY ELECTRIC Co.,Ltd.

<https://www.stanley.co.jp/e/product/>

Contact

Germany :Stanley Electric GmbH
UK :Stanley Electric (U.K.) Co., Ltd.
France :STANLEY-IDESS S.A.S.
Web :<https://www.stanley.co.jp/e/inquiry/>

Waldecker Strasse 5 D-64546 Moerfelden-Walldorf, Germany, EU
The Columbia Centre, Station Road, Bracknell, Berkshire RG12 1PL, U.K.
41, rue des Trois Fontanot, 92000 Nanterre, France

(Tel: 49-6105-930530 Fax: 49-6105-930555)
(Tel: 44-1344-830450 Fax: 44-1344-830496)
(Tel: 33-1-4781-8585 Fax: 33-1-4786-0916)