
























MULTICOLOR LEDs

























パッケージ Package	品名 Part name	電気的光学的特性/Electro-optical characteristics										絶対最大定格/Absolute maximum ratings					標準梱包 数量 Standard qty./Reel	WEB				
		発光色 Emitted color	色度座標 Chromaticity coordinates <sup>*1</sup>		ドミナント発光波長 Dominant wavelength $\lambda_d$ Typ.	発光光度 Luminous intensity		順電圧 Forward voltage		指向半値角 Half-intensity angle $2\theta_{1/2}$ ( $\theta_x/\theta_y$ )	指向特性 Spatial distribution	選別電流 Sorting current $I_F$	順電流 Forward current $I_F$	順電流低減率 Forward current decrease rate		動作温度 Operating temperature Topr			保存温度 Storage temperature Tstg			
			x Typ.	y Typ.		Min.	Typ.	Typ.	Max.					$\Delta I_F$	Derating start temp. °C							
単位 (Units)		-		nm	mcd		V		deg.	-	mA	mA	mA/°C	°C	°C	°C	pcs.					
 L1.6 x W1.5 x H0.7 3mg FRYPY1211C-0005		-	-	570	6.3	12	1.95	2.4	115 / 140		5	15	0.21	25	-40~+85	-40~+100	4,000					
		-	-	626	14	30	1.85	2.4														
 L3.0 x W2.5 x H1.5 13mg DRD1204W		-	-	572	70	130	2.0	2.4	$\theta_x 60$		20	30	0.43	25	-40~+85	-40~+100	2,500					
		-	-	626	100	184	2.0	2.4	$\theta_x 70$													
 L2.04 x W2.04 x H0.6 3.4mg ARGB1314HSE		-	-	468	125	175	3.0	3.5	120/140		20	25	0.714	80	-40~+115	-40~+115	4,000					
		-	-	527	650	900	3.0	3.6	120/140										20	25	0.714	80
		-	-	622	320	440	2.1	2.7	120/140										20	30	0.857	80
 L3.0 x W2.8 x H0.6 10mg CRGB1314ASE-500		-	-	469	100	300	3.1	3.7	120 / 120		14	25	0.65	80	-40~+100	-40~+120	4,000					
		-	-	532	1,500	2,080	3.2	3.9											23	25	0.65	80
		-	-	622	560	820	2.1	2.8											22	30	0.75	80
		0.300	0.320	-	2,060	3,100	-	-											-	-	-	-

\*製品画像は代表的なものです/All pictures shown are for illustration purposes only. Actual product may vary due to product enhancement.

\*1 CIE1931に基づく/In accordance with CIE1931

\*2 2色または3色点灯時/When two or three LEDs with different colors are illuminated

MULTICOLOR LEDs

パッケージ Package	品名 Part name	電気的光学的特性/Electro-optical characteristics										絶対最大定格/Absolute maximum ratings					標準梱包 数量 Standard qty./Reel	WEB	
		発光色 Emitted color	色度座標 Chromaticity coordinates <sup>*1</sup>		ドミナント発光波長 Dominant wavelength $\lambda_d$ Typ.	発光光度 Luminous intensity		順電圧 Forward voltage $V_F$		指向半値角 Half-intensity angle $2\theta_{1/2}$ ( $\theta_x/\theta_y$ )	指向特性 Spatial distribution	選別電流 Sorting current $I_F$	順電流 Forward current $I_F$	順電流低減率 Forward current decrease rate $\Delta I_F$		動作温度 Operating temperature Topr			保存温度 Storage temperature Tstg
			x Typ.	y Typ.		Min.	Typ.	Typ.	Max.					mA/°C	°C				
単位 (Units)		-		nm	mcd		V		deg.	-	mA	mA	mA/°C	°C	°C	°C	pcs.		
L2.04 x W2.04 x H0.6  3.4mg	ARGB1313HS		-	-	473	-	180	3.1	3.8	125 / 145		12	30	0.750	60	-40~+85	-40~+100	4,000	
			-	-	527	-	850	3.2	3.8			22	30	0.750	60				
			-	-	622	-	450	2.1	2.8			26	30	0.750	60				
			0.300	0.320	-	-	1,350	-	-		-	Blue : 12 Green : 22 Red : 26	Blue : 20 Green : 25 Red : 30	-	-				
L3.0 x W2.8 x H0.7  9.4mg	ARGB131CWSE-10		-	-	467	-	250	3.0	3.8	120 / 120		14	30	0.750	60	-40~+85	-40~+100	4,000	
			-	-	527	-	2,000	2.7	3.5	120 / 120		18	30	0.750	60				
			-	-	621	-	850	2.1	2.8	120 / 120		26	30	0.750	60				
			0.300	0.320	-	-	3,000	-	-	-	Blue : 14 Green : 18 Red : 26	Blue : 20 Green : 25 Red : 30	-	-					
L1.1 x W4.5 x H1.5  14mg	ARGB131DFSE-10		-	-	467	-	250	3.0	3.8	110 / 110		15	30	0.750	60	-40~+85	-40~+100	2,500	
			-	-	527	-	2,000	2.7	3.5	110 / 110		17	30	0.750	60				
			-	-	621	-	900	2.1	2.8	110 / 110		26	30	0.750	60				
			0.300	0.320	-	-	3,050	-	-	-	Blue : 15 Green : 17 Red : 26	Blue : 20 Green : 25 Red : 30	-	-					

※製品画像は代表的なものです/All pictures shown are for illustration purposes only. Actual product may vary due to product enhancement.

※1 CIE1931に基づく/In accordance with CIE1931

※2 2色または3色点灯時/When two or three LEDs with different colors are illuminated